

SPECIFICATIONS

Customer	
Product Name	Wire Wound SMD Power Inductor
A-PLUS Part Number	SWPA252012S Series
Customer Part Number	

New Released Revised

SPEC No.: SWPA02130000

【This SPEC is total 11 pages.】

【ROHS Compliant Parts】

Approved By	Checked By	Issued By

A-PLUS POWER TECHNOLOGY CO., LTD.

【For Customer approval Only】

Date: _____

Qualification Status: Full Restricted Rejected

Approved By	Verified By	Re-checked By	Checked By

Comments:

【Version change history】

Rev.	Effective Date	Changed Contents	Change Reasons	Approved By
01	/	New released	/	Qintian Hou

1 Scope


This specification applies to the SWPA252012S Series of wire wound SMD power inductor.

2 Product Description and Identification (Part Number)

1) Description:

SWPA252012S series of Wire wound SMD power inductor.

2) Product Identification (Part Number)



①	Type
SWPA	Wire wound SMD power inductor

②	External Dimensions(LxWxH) [mm]	
252012	2.5X2.0X 1.2	

③	Feature type
S	Standard Type

④	Nominal Inductance	
Example	Example	
1R0	1.0uH	
100	10uH	
101	100uH	

⑤	Inductance Tolerance	
N	±30%	
M	±20%	

⑦	Special Process code	
□□□	Special Process code	
* Standard product is blank		

⑥	Packing	
T	Tape Carrier Package	

3 Electrical Characteristics

Please refer to **Item 12**.

- 1) Operating and storage temperature range (individual chip without packing): -40°C ~ +125°C (Including Self-heating)
- 2) Storage temperature range (packaging conditions): -10°C ~ +40°C and RH 70% (Max.)

4 Test and Measurement Procedures

Test Conditions

Unless otherwise specified, the standard atmospheric conditions for measurement/test as:

- a. Ambient Temperature: 20±15°C
- b. Relative Humidity: 65±20%
- c. Air Pressure: 86kPa to 106kPa

If any doubt on the results, measurements/tests should be made within the following limits:

- a. Ambient Temperature: 20±2°C
- b. Relative Humidity: 65±5%
- c. Air Pressure: 86kPa to 106kPa

Visual Examination

Inspection Equipment: 10X microscope

Electrical Test

Inductance (L)

- a. Refer to **Item 12**. Test equipment: WK3260B LCR meter or equivalent.
- b. Test Frequency and Voltage: refers to **Item 12**.

Direct Current Resistance (DCR)

- a. Refer to **Item 12**.
- b. Test equipment: HIOKI 3540 or equivalent.

Saturation Current (Isat)

- a. Refer to **Item 12**.
- b. Test equipment: WK3260B LCR meter or equivalent.
- c. Definition of saturation current (Isat): DC current at which the inductance drops approximate 30% from its value without current.

Temperature rise current (Irms)

- a. Refer to **Item 12**.
- b. Test equipment (see **Fig. 4.3.4-1, Fig. 4.3.4-2**): Electric Power, Electric current meter, Thermometer.
- c. Measurement method
 - 1. Set test current to be 0 mA.
 - 2. Measure initial temperature of choke surface.
 - 3. Gradually increase current and measure choke temperature for corresponding current.
 - 4. Definition of Temperature rise current: DC current that causes the temperature rise ($\Delta T = 40^\circ C$) from 20°C ambient




Fig. 4.3.4-1




Fig. 4.3.4-2

5 Shape and Dimensions

Dimensions and recommended PCB pattern for reflow soldering, please see Fig.5-1, Fig. 5-2 and Table 5-1.




Fig.5-1,

[Table 5-1] (Unit: mm)

Series	A	B	C.	D	E	F	a.	b	c
SWPA252012S	2.5±0.1	2.0±0.1	1.2Max.	1.5±0.2	0.80±0.2	0.80±0.2	0.80Typ.	0.85Typ.	2.0Typ.




Fig.5-2

Δf: Clearance between terminal and the surface of plate must be 0.1mm max when coil is placed on a flat plate.

6 Structure

The structure of SWPA252012S product, please refer to Fig.6-1 and Table 6-1.




Fig. 6-1




[Table 6-1]


No.	Components	Material
①	Ferrite Core	Ni-Zn Ferrite
②	Wire	Polyurethane system enameled copper wire
③	Magnetic Glue	Epoxy resin and magnetic powder
④	Plating Electrodes	Plating: Ag/Ni/Sn
⑤	Outer Electrodes	Top surface solder coating: Sn96.5%/Ag3.0%/Cu0.5%

7 Product Marking

N/A

8 Reliability Test

Items	Requirements	Test Methods and Remarks
8.1 Terminal Strength	No removal or split of the termination or other defects shall occur.  <p style="text-align: center;">Fig.8.1-1</p>	① Solder the inductor to the testing jig (glass epoxy board shown in Fig.8.1-1) using eutectic solder. Then apply a force in the direction of the arrow. ② 10N force. ③ Keep time: 5s
8.2 Resistance to Flexure	No visible mechanical damage.  <p style="text-align: center;">Fig.8.2-1</p>	① Solder the chip to the test jig (glass epoxyboard) using eutectic solder. Then apply a force in the direction shown as Fig.8.2-1 . ② Flexure: 2mm ③ Pressurizing Speed: 0.5mm/sec ④ Keep time: 30±1s ⑤ Test board size: 100X40X1.0 ⑥ Land dimension: Please see Fig.5-1
8.3 Vibration	① No visible mechanical damage. ② Inductance change: Within ±10%	① Solder the chip to the testing jig (glass epoxy board shown as the following figure) using eutectic solder. ② The chip shall be subjected to a simple harmonic motion having total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10 and 55 Hz. ③ The frequency range from 10 to 55 Hz and return to 10 Hz shall be traversed in approximately 1 minute. This motion shall be applied for a period of 2 hours in each 3 mutually perpendicular directions (total of 6 hours).
8.4 Temperature coefficient	Inductance change: Within ±20%	① Temperature: -40℃~+125℃ ② With a reference value of +20℃, change rate shall be calculated
8.5 Solderability	90% or more of electrode area shall be coated by new solder.	① The test samples shall be dipped in flux, and then immersed in molten solder. ② Solder temperature: 245±5℃ ③ Duration: 5±1 sec. ④ Solder: Sn/3.0Ag/0.5Cu ⑤ Flux: 25% resin and 75% ethanol in weight ⑥ Immersion depth: all sides of mounting terminal shall be immersed
8.6 Resistance to Soldering Heat	① No visible mechanical damage. ② Inductance change: Within ±10%	① Re-flowing Profile: Please refer to Fig. 8.6-1 . ② Test board thickness: 1.0mm ③ Test board material: glass epoxy resin ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring  <p style="text-align: right;">Fig. 8.6-1</p>

<p>8.7 Thermal Shock</p>	<p>① No visible mechanical damage. ② Inductance change: Within $\pm 10\%$</p>  <p style="text-align: center;">Fig.8.7-1</p>	<p>① Temperature and time: $-40\pm 3^{\circ}\text{C}$ for 30 ± 3 min $\rightarrow 125^{\circ}\text{C}$ for 30 ± 3 min, please refer to Fig. 8.7-1. ② Transforming interval: Max. 20 sec ③ Tested cycle: 100 cycles ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>8.8 Resistance to Low Temperature</p>	<p>① No visible mechanical damage ② Inductance change: Within $\pm 10\%$</p>	<p>① Temperature: $-40\pm 3^{\circ}\text{C}$ ② Duration: $1000^{\pm 24}$ hours ③ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>8.9 Resistance to High Temperature</p>	<p>① No mechanical damage. ② Inductance change: Within $\pm 10\%$</p>	<p>① Temperature: $125\pm 2^{\circ}\text{C}$ ② Duration: $1000^{\pm 24}$ hours ③ The chip shall be stabilized at normal condition for 1~2 hours before measuring.</p>
<p>8.10 Damp Heat</p>	<p>① No mechanical damage. ② Inductance change: Within $\pm 10\%$</p>	<p>① Temperature: $60\pm 2^{\circ}\text{C}$ ② Humidity: 90% to 95%RH ③ Duration: $1000^{\pm 24}$ hours ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>8.11 Loading Under Damp Heat</p>	<p>① No mechanical damage. ② Inductance change: Within $\pm 10\%$</p>	<p>① Temperature: $60\pm 2^{\circ}\text{C}$ ② Humidity: 90% to 95% RH ③ Applied current: Rated current ④ Duration: $1000^{\pm 24}$ hours ⑤ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>8.12 Loading at High Temperature</p>	<p>① No mechanical damage. ② Inductance change: Within $\pm 10\%$</p>	<p>① Temperature: $85\pm 2^{\circ}\text{C}$ ② Applied current: Rated current ③ Duration: $1000^{\pm 24}$ hours ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>

9 Packaging, Storage and Transportation

Tape and Reel Packaging Dimensions

Taping Dimensions (Unit: mm)

Please refer to **Fig. 9.1.1** and **Table 9.1.1**.




Fig9.1.1

[Table9.1.1]

Series	A ₀	B ₀	W	E	F	P ₀	P ₁	P ₂	D ₀	T	K ₀
SWPA252012S	2.35±0.05	2.65±0.05	8±0.3	1.75±0.1	3.5±0.05	4.0±0.1	4.0±0.1	2.0±0.1	1.5+0.1/-0.0	0.25±0.03	1.4±0.1

Direction of rolling Please refer to Fig. 9.1.2




Fig. 9.1.2.

Reel Dimensions (Unit: mm)
Please refer to Fig. 9.1.3.




Fig. 9.1.3

Top tape strength
Peel-off strength: 10~100gf.
Peel-off angle: $165^\circ \sim 180^\circ$, refers to Fig.9.1.4.
Peel-off speed: 300mm/min.




Fig. 9.1.4

The number of components
A tape & reel package contains 2000 inductors.
The allowable number of empty chip cavities
Maximum two (2) chip cavities missing product may exist in a reel but they may not be consecutive two cavities.

Packing Documents and Marking

Packing Documents

Packing documents include the following:

- 1) Packaging list
- 2) Certificate of compliance (COC)

9.2.2 Packing QTY.

- 1) Inner Box: 10 reel in each box.
- 2) Outer Box: 4 or 8 inner boxes in each outer case.
- 3) 40 or 80 reels in each outer case.

9.2.3 Marking

1) Marking label information on reels includes (see Fig.9.2.3-1, Fig.9.2.3-2A/2B):

- a). A-PLUS P/N.
- b). Quantity per reel
- c). Lot number
- d). Inspection No.
- e). Inspection stamp
- f). MFG address as 'Made In China'




Fig.9.2.3-1




Fig.9.2.3-2A




Fig.9.2.3-2B

2) Marking label information on inner box

- a). Inner box please refers to Fig.9.2.3-3 and Table 9.2.3-1
- b). Marking Label on inner box (see Fig.9.2.3-4)

3) Marking on outer case (see Fig.9.2.3-5~7):

Out case size please refers to Table 9.2.3-2.

- a). Manufacturer: A-PLUS ID:
"A-PLUS POWER Technology Co., Ltd."
- b). Packing label include the following:
 - i) Customer
 - ii) Manufacturer
 - iii) Date code
 - iv) C/No.

Example: "1/10" means that this case is the 1st one of total 10 cases

- v) P/O No.
- vi) Customer Part No.
- vii) A-PLUS Part No.
- viii) Quantity.
- ix) Inspection Stamp.




Fig.9.2.3-3

Packaging type	A(mm)	B(mm)	C(mm)
Inner box	180	120	180

[Table 9.2.3-1]

Packaging type	L(mm)	W(mm)	H(mm)
Type1	505	378	200
Type2	380	260	200

[Table 9.2.3-2]




Fig.9.2.3-4




Fig. 9.2.3-5



Fig.9.2.3-6











Fig.9.2.3-7

10 Visual inspection standard of product

File No:		Applied to Wire Wound SMD Power Inductor Series		REV:01
Effective date:				
No.	Defect Item	Graphic	Rejection identification	Acceptance
1	Core defect		The defect length/width (l or w) more than $L/6$ or $W/6$, NG.	AQL=0.65
2	Core crack		Visual cracks, NG.	AQL=0.65
3	Starvation		① Resin starved length, l , more than $L/2$, NG. ② IF $W \geq 2\text{mm}$, resin starved width, w , more than $W/2$, NG. ③ IF $W < 2\text{mm}$, resin starved width, w , don't control.	AQL=0.65
4	Excessive glue		The length, width or height of product beyond specified value, NG.	AQL=0.65
5	Cold solder		① For SWPA252012S, cold solders l more than 0.5 mm, NG. ② For other series, cold solders l more than 1 mm, NG.	AQL=0.65
6	Solder icicle		① The height H of product beyond specified value, NG; ② The clearance Δf beyond specified value listed in Item 5, NG;	AQL=0.65
7	Electrode uneven		The clearance Δf beyond specified value listed in Item 5, NG;	AQL=0.65

11 Recommended Soldering Technologies

11.1 Re-flowing Profile:

- △ Preheat condition: 150 ~200°C/60~120sec.
 - △ Allowed time above 217°C: 60~90sec.
 - △ Max temp: 260°C
 - △ Max time at max temp: 5sec.
 - △ Solder paste: Sn/3.0Ag/0.5Cu
 - △ Allowed Reflow time: 2x max
- Please refer to Fig. 11.1-1.




Fig. 11.1-1


[Note: The reflow profile in the above table is only for qualification and is not meant to specify board assembly profiles. Actual board assembly profiles must be based on the customer's specific board design, solder paste and process, and should not exceed the parameters as the Reflow profile shows.]

11.2 Iron Soldering Profile

- △ Iron soldering power: Max. 30W
- △ Pre-heating: 150°C/60sec.
- △ Soldering Tip temperature: 350°C Max.
- △ Soldering time: 3sec. Max.
- △ Solder paste: Sn/3.0Ag/0.5Cu
- △ Max.1 times for iron soldering

Please refer to Fig. 11.2-1.

[Note: Take care not to apply the tip of the soldering iron to the terminal electrodes.]




12 Electrical Characteristics

Fig. 11.2-1


Part Number	Inductance	Inductance Test Condition	DC Resistance (± 30%)		Min. Self-resonant Frequency	Max. Saturation Current		Max. Heat Rating Current
			Max.	Typ.		Max.	Typ.	
Units	μH	-	Ω	Ω	MHz	A	A	A
Symbol	L	-	DCR		S.R.F	Isat		Irms
SWPA252012SR47NT	0.47±30%	100KHz,1V	0.056	0.047	160	3.82	4.27	2.15
SWPA252012SR68NT	0.68±30%	100KHz,1V	0.068	0.057	140	3.28	3.68	1.95
SWPA252012S1R0NT	1.0±30%	100KHz,1V	0.083	0.069	110	2.59	2.90	1.93
SWPA252012S1R2NT	1.2±30%	100KHz,1V	0.119	0.099	100	2.38	2.67	1.46
SWPA252012S1R5MT	1.5±20%	100KHz,1V	0.136	0.113	97	2.24	2.51	1.40
SWPA252012S1R5NTY01	1.5±30%	100KHz,1V	0.120	0.100	63	1.80	2.00	1.45
SWPA252012S2R2MT	2.2±20%	100KHz,1V	0.199	0.166	69	1.85	2.07	1.15
SWPA252012S2R2NTY02	2.2±30%	100KHz,1V	0.142	0.118	53	1.55	1.75	1.30
SWPA252012S2R7MT	2.7±20%	100KHz,1V	0.221	0.184	63	1.72	1.92	1.09
SWPA252012S3R3MT	3.3±20%	100KHz,1V	0.244	0.203	62	1.61	1.80	1.04
SWPA252012S3R6MT	3.6±20%	100KHz,1V	0.322	0.268	53	1.46	1.64	0.90
SWPA252012S4R3MT	4.3±20%	100KHz,1V	0.348	0.290	51	1.37	1.53	0.87
SWPA252012S4R7MT	4.7±20%	100KHz,1V	0.348	0.290	47	1.12	1.25	0.84
SWPA252012S5R1MT	5.1±20%	100KHz,1V	0.462	0.385	44	1.23	1.37	0.75
SWPA252012S5R6MT	5.6±20%	100KHz,1V	0.497	0.414	38	1.11	1.25	0.73
SWPA252012S6R2MT	6.2±20%	100KHz,1V	0.500	0.417	38	1.03	1.16	0.73
SWPA252012S6R8MT	6.8±20%	100KHz,1V	0.536	0.447	38	0.98	1.09	0.69
SWPA252012S7R5MT	7.5±20%	100KHz,1V	0.564	0.470	35	0.97	1.09	0.68
SWPA252012S8R2MT	8.2±20%	100KHz,1V	0.607	0.506	36	0.98	1.10	0.65
SWPA252012S9R1MT	9.1±20%	100KHz,1V	0.637	0.531	34	0.91	1.02	0.62
SWPA252012S100MT	10±20%	100KHz,1V	0.637	0.531	34	0.79	0.88	0.62
SWPA252012S120MT	12±20%	100KHz,1V	0.992	0.827	28	0.78	0.88	0.51
SWPA252012S150MT	15±20%	100KHz,1V	1.469	1.224	25	0.68	0.77	0.42
SWPA252012S220MT	22±20%	100KHz,1V	1.824	1.520	20	0.53	0.59	0.38

Typical Electrical Characteristics

Temperature vs. DC Current Characteristics



Inductance vs. DC Current Characteristics



13 Precautions

Surface mounting

- Mounting and soldering condition should be checked beforehand.
- Applicable soldering process to this product is reflow soldering only.
- Recommended conditions for repair by soldering iron:
Preheat the circuit board with product to repair at 150°C for about 1 minute.
Put soldering iron on the land-pattern.
Soldering iron's temperature: 350°C maximum/Duration: 3 seconds maximum/1 time for each terminal.
The soldering iron should not directly touch the inductor.
Product once removes from the circuit board may not be used again.

Handling

- Keep the products away from all magnets and magnetic objects.
- Be careful not to subject the products to excessive mechanical shocks.
- Please avoid applying impact to the products after mounted on pc board.
- Avoid ultrasonic cleaning.

Storage

- To maintain the solderability of terminal electrodes and to keep the packing material in good condition, temperature and humidity in the storage area should be controlled.
- Recommended conditions: -10°C~40°C, 70%RH (Max.)
- Even under ideal storage conditions, solderability of products electrodes may decrease as time passes. For this reason, product should be used with one year from the time of delivery.
- In case of storage over 6 months, solderability shall be checked before actual usage.

Regarding Regulations

- Any Class- I or Class- II ozone-depleting substance (ODS) listed in the Clean Air Act in US for regulation is not included in the products or applied to the products at any stage of whose manufacturing processes.
- Certain brominated flame retardants (PBBs, PBDEs) are not used at all.
- The products of this specification are not subject to the Export Trade Control Order in China or the Export Administration Regulations in US.

Guarantee

- The guaranteed operating conditions of the products are in accordance with the conditions specified in this specification.
- Please note that A-PLUS takes no responsibility for any failure and/or abnormality which is caused by use under other than the aforesaid operating conditions.

14 Supplier Information

Supplier:

A-PLUS POWER TECHNOLOGY CO., LTD.